

Packaging, POP & Signage

from The Garvey Group

KBA Rapida 105 (10 color)

Typical Uses:

- Brochures
- Catalogs
- Manuals
- Coupons
- Direct Mail
- Posters
- Custom Made Product Boxes

Wide array of substrates stocked:

- 60, 70 and 80# Coated (Roll and Sheet Fed)
- 50, 60 and 70# Offset
- 8 and 10 pt C1S and C2S
- 100# Coated Cover

Substrate Printing Materials:

From .003" to .048" including paper and board

Maximum Sheet Size:

Inline	29.125" x 41.313"
Perfecting	28.156" x 41.313"

Minimum Sheet Size:

Inline	13.375" x 18.906"
Perfecting	15.750" x 18.906"

Maximum Image:

Inline	28.625" x 40.875"
Perfecting	27.000" x 40.875"

Minimum Caliper	
Inline:	0.003"
Perfecting:	0.003"
Maximum Caliper:	
Inline:	0.048"
Perfecting:	0.024"
Sheets Per Hour:	12,000
Gripper:	0.406"
Number of Printing Units:	10 printing units
Number of Coating Units:	1 (15' extended delivery)
Types of Coatings:	Matte, Dull, Gloss, Aqueous and UV
Types of Printing:	Conventional and UV
CIP3 Software:	Presets inks & water at the time of rip to the plate setter
KBA Densitronic:	Sheet scanner using both spectrometer and densitometer to control quality
Screen Ultima 36000 Plate Setter:	Maximum size 60" x 81"
HP 5560 Matchprint Inkjet Proofer:	6 colors, 60" x 81", 360 DPI
Kodak XP4 Approval Proofer:	Maximum size 20.8" x 26.6" 2400 DPI
Rip:	Nexus